



## TL12-17(12V17AH/20HR)




### Specifications

Nominal Voltage		12V
Rated capacity (20hour rate)		17Ah
Dimensions	Total Height	167 mm (6.57 inches)
	Height	167 mm (6.57 inches)
	Length	181 mm (7.13 inches)
	Width	77 mm (3.03 inches)
Weight Approx		5.0Kg


### Characteristics

Capacity 25°C(77°F)	20 hour rate(0.85A)	17.0AH
	10 hour rate(1.56A)	15.6AH
	5 hour rate(2.89A)	14.45AH
	1 hour rate(10.2A)	10.2AH
Internal Resistance	Full charged Battery at 25°C(77°F)	11.5 mΩ
Capacity affected by Temperature (20hour rate)	40°C(104°F)	102%
	25°C(77°F)	100%
	0°C(32°F)	85%
	-15°C(5°F)	65%
Self-Discharge at 25°C(77°F)	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
	Capacity after 12 month storage	64%
Terminal	T3, T13	
Charge (constant Voltage)	Cycle	Initial Charging Current less than 4.80A Voltage 14.40-14.70V
	Float	Voltage 13.50-13.80V


### Outer dimensions (mm)



### Terminal Type (mm)



### Discharge Curves 25°C(77°F)



**Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25°C(77°F)**

Time		5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
9.60V	A	64.8	42.5	31.5	20.7	10.80	6.30	4.64	3.72	3.16	2.08	1.70	0.93
	W	764.2	480.0	363.0	219.7	124.5	72.9	53.63	43.05	36.53	24.08	19.72	10.80
10.20V	A	59.4	40.6	28.9	19.7	10.14	6.04	4.50	3.60	3.10	2.05	1.67	0.91
	W	719.2	454.5	341.2	218.3	117.0	70.0	52.12	41.70	35.85	23.70	19.35	10.50
10.50V	A	54.1	38.0	27.0	19.0	9.81	5.93	4.42	3.42	3.06	2.03	1.66	0.90
	W	694.5	441.0	326.3	216.0	113.5	68.6	51.22	39.60	35.63	23.48	19.20	10.43
10.80V	A	52.0	36.3	25.2	18.5	9.48	5.77	4.35	3.36	2.93	1.97	1.61	0.88
	W	609.0	427.5	314.2	215.2	110.3	67.2	50.63	39.11	34.05	22.50	18.75	10.20
11.10V	A	48.1	34.2	23.4	18.0	9.15	5.63	4.13	3.30	2.80	1.92	1.58	0.86
	W	588.7	413.2	299.3	213.8	108.8	66.7	49.13	39.00	33.30	21.75	18.37	10.13

