



SENSITIVE GATE SILICON CONTROLLED RECTIFIERS

DESCRIPTION

PNPN devices designed for high volume, line-powered consumer applications such as relay and lamp drivers, small motor controls, gate drivers for larger thyristors, and sensing and detection circuits.

FEATURES

- Sensitive gate allows triggering by micro controllers and other logic circuits
- Blocking voltage to 400V
- On-state current rating of 3.0A RMS at 80°C
- High surge current capability – 20A
- Minimum and maximum values of IGT, VGT and IH specified for ease of design
- Immunity to dV/dt – 10V/ μ sec minimum at 110°C
- Glass-passivated surface for reliability and uniformity



ABSOLUTE MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ UNLESS OTHERWISE SPECIFIED)


Symbol	Parameter	Condition	Ratings	Units
VDRM	Repetitive Peak Off-State Voltage		400	V
$I_T(AV)$	Average On-State Current	Half Sine Wave : $T_C = 74^\circ\text{C}$	2.0	A
$I_T(RMS)$	R.M.S On-State Current	All Conduction Angle	3.0	A
ITSM	Surge On-State Current	1/2 Cycle, 60Hz, Sine Wave Non-Repetitive	10	A
I^2t	I^2t for Fusing	$t = 10.0\text{ms}$	1.615	A^2S
PGM	Forward Peak Gate Power Dissipation		0.5	W
PG(AV)	Forward Average Gate Power Dissipation		0.1	W
IFGM	Forward Peak Gate Current		0.2	A
T_J	Operating Junction Temperature		- 40 ~ 110	$^\circ\text{C}$
TSTG	Storage Temperature		- 40 ~ 150	$^\circ\text{C}$

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	Junction to Case	TO-251	15	$^\circ\text{C}/\text{W}$
$R_{th(j-a)}$	Junction to Ambient	TO-251	100	$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ($T_C = 25\text{ }^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Symbol	Items	Conditions	Ratings			Unit
			Min.	Typ.	Max.	
I_{DRM}	Repetitive Peak Off-State Current	$V_{AK} = V_{DRM}$ or V_{RRM} ; $T_C = 25\text{ }^\circ\text{C}$ $T_C = 125\text{ }^\circ\text{C}$	—	—	5 100	μA
V_{TM}	Peak On-State Voltage	($I_{TM} = 4\text{ A}$, Peak)	—	1.2	1.7	V
I_{GT}	Gate Trigger Current	$V_D = 12\text{ V}$	—	—	200	μA
V_{GT}	Gate Trigger Voltage	$V_D = 12\text{ V}$	—	—	0.8	V
V_{GD}	Non-Trigger Gate Voltage	$V_D = V_{DRM}$, $R_{GK} = 1000\text{ohm}$, $R_L = 3.3\text{Kohm}$, $T_J = 110\text{ }^\circ\text{C}$	0.2	—	—	V
dv/dt	Critical Rate of Rise Off-State Voltage	$V_D = 2/3 V_{DRM}$, $R_{GK} = 1000\text{ohm}$, $T_J = 110\text{ }^\circ\text{C}$	10	—	—	V/ μS
di/dt	Critical Rate of Rise Off-State Voltage	$I_{PK} = 20\text{ A}$; $di/dt = 1\text{ A}/\mu\text{S}$; $I_{gt} = 20\text{ mA}$	—	—	50	A/ μS
I_H	Holding Current	$I_T = 0.05\text{ A}$	—	—	5.0	mA

VOLTAGE CURRENT CHARACTERISTIC OF SCR


PACKAGE MECHANICAL DATA

Symbol	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.10	2.40	0.083	0.094
A1	0.89	1.50	0.035	0.059
b	0.50	0.70	0.020	0.028
b1	0.70	0.90	0.028	0.035
b2	5.20	5.40	0.205	0.213
C	0.46	0.61	0.018	0.024
C1	0.46	0.89	0.018	0.035
D	6.35	6.73	0.250	0.265
E	5.33	6.30	0.210	0.248
e	2.29TYP		0.09TYP	
L	6.50	7.90	0.256	0.311
L1	1.42	1.82	0.056	0.072
L2	1.35	1.65	0.053	0.065

CONTACT US

Headquarters
 A Building Caohejing I&E Park
 Pujiang Minhang Shanghai
 China

Web
<http://www.semiwill.com>

By Telephone
 General: 86-21-34637654
 Sales: 86-21-34637458
 Customer Service: 86-21-34637172

By Email
 Sales: sales@semiwill.com
 Customer Service: cs@semiwill.com
 Technical Support: fae@semiwill.com

By Fax
 General: 86-21-34637173
 Sales: 86-21-39650654

COPYRIGHT ©SEMIWILL 2009 - This literature is subject to all applicable copyright laws and is not for resale in any manner.

SPECIFICATIONS: SEMIWILL reserves the right to change the electrical and or mechanical characteristics described herein without notice.

DESIGN CHANGES: SEMIWILL reserves the right to discontinue product lines without notice and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance. SEMIWILL assumes no responsibility with respect to the selection or specifications of such products. SEMIWILL makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SEMIWILL assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability without limitation special, consequential or incidental damages.

LIFE SUPPORT POLICY: SEMIWILL products are not authorized for use in life support systems without written consent from the factory.