

SHENZHEN BRILLIANT CRYSTAL TECHNOLOGIC CO.,LTD.

深 圳 市 彩 晶 科 技 有 限 公 司

The specification for the following models :

CM802-6BLWAA-5**CM802-6FLWAA-5**

PROPOSED BY		APPROVED
Design	Approved	

TEL:+86-755-29995238

FAX:+86-755-29459900

Http://www.cj86.com

E-mail:szcj86@gmail.com

Http://www.szcm-lcd.com


E-mail:szcj86@hotmail.com

地址：深圳市南山区西丽留仙洞工业区顺和达厂区 B 栋

1. Mechanical Specification

ITEM	STANDARD VALUE			UNIT
NUMBER OF CHARACTERS	8 CHARACTERS X 2 LINES			--
CHARACTER FORMAT	5 X 8 DOTS			--
MODULE DIMENSION	58.0 (W) X 32.0 (H) X 13.5 (T)			mm
VIEWING DISPLAY AREA	38.0 (W) X 16.0 (H)			mm
ACTIVE DISPLAY AREA	27.81 (W) X 11.5 (H)			mm
CHARACTER SIZE	2.96 (W) X 5.56 (H)			mm
CHARACTER PITCH	3.55 (W) X 5.94 (H)			mm
DOT SIZE	0.56 (W) X 0.66 (H)			mm
DOT PITCH	0.04 (W) X 0.04 (H)			mm
DRIVE METHOD	1/16 Duty , 1/5BIAS			
VIEWING DIRECTION	6 O'clock			
LED Backlight Color	White			
Backlight Input	DC +5.0V	V		mA
LED backlight current	10			mA
Backlight Half-Lift Time	35,000			HR.
INPUT VOLAGE	DC +5.0V	V	1	mA
LCD DRIVER	SPLC780D			
Weight	24g			

2. Mechanical Diagram



3. Interface Pin Connections

NO	SYMBOL	LEVEL	FUNCTION
1	VSS	--	GND (0V)
2	VDD	--	DC +5V
3	VO	--	Contrast Adjust
4	RS	H/L	Register select
5	R/W	H/L	Read/Write
6	E	H,H→L	Enable signal
7	DB0	H/L	Data Bit 0
8	DB1	H/L	Data Bit 1
9	DB2	H/L	Data Bit 2
10	DB3	H/L	Data Bit 3
11	DB4	H/L	Data Bit 4
12	DB5	H/L	Data Bit 5
13	DB6	H/L	Data Bit 6
14	DB7	H/L	Data Bit 7
15	LED A	--	+5V (LED Backlight 1)
16	LED K	--	0V(LED Backlight 2)

4. Absolute Maximum Ratings

ITEM	SYMBOL	MIN.	TYPE	MAX.	UNIT
OPERATING TEMPERATURE	TOP	0/-20	--	+50/+70	
STORAGE TEMPERATURE	TST	-10/-30	--	+60/+80	
INPUT VOLTAGE	VI	4.75	5.0	5.25	V
SUPPLY VOLTAGE FOR LOGIC	VDD-VSS	--	5.0	5.5	V
SUPPLY VOLTAGE FOR LCD	VDD-VO	--	--	5.0	V
STATIC ELECTRICITY	Be sure that you are grounded when handing LCM.				