



Size: 172mmx150mmx51mm  
 Weight: 880 g  
 Impeller: PA6 UL94V-0 Reinforced Plastic  
 Frame: Aluminum Alloy  
 Motor: Shaded Pole Induction Motor



Safety Approvals				
	CE	UL	CUL	TUV
100~125	●	●	●	●
220~240	●	●	●	●

### 温馨提示

我司可定做特殊风扇如：防潮、防水、涡轮增压、软起动、正反转、无极温控、PWM 调速、连接端子、RD 报警和 FG 信号，有需要请与我司销售代表联络，谢谢!

Listed Model	Bearing System	Voltage	Freq.	Current	Power	Speed	Noise	Air Flow		Static Pressure
		VAC	Hz	A	W	RPM	dBA	m3/hr	CFM	(mmH2O)
XHA17251S22H	Sleeve	220~240	50/60	0.40	47/41	2700/3000	51/55	272/306	160/180	11.3/13
XHA17251S22M		220~240	50/60	0.30	28/27	2500/2700	49/51	252/272	148/160	9.9/7.0
XHA17251S22L		220~240	50/60	0.20	20/20	2200/2400	45/47	233/240	137/141	3.4/4.6
XHA17251B22H	Ball	220~240	50/60	0.40	47/41	2700/3000	51/55	272/306	160/180	11.3/13
XHA17251B22M		220~240	50/60	0.30	28/27	2500/2700	49/51	252/272	148/160	9.9/7.0
XHA17251B22L		220~240	50/60	0.20	20/20	2200/2400	45/47	233/240	137/141	3.4/4.6
XHA17251S11H	Sleeve	100~125	50/60	0.60	47/41	2700/3000	51/55	272/306	160/180	11.3/13
XHA17251S11M		100~125	50/60	0.50	28/27	2500/2700	49/51	252/272	148/160	9.9/7.0
XHA17251S11L		100~125	50/60	0.40	20/20	2200/2400	45/47	233/240	137/141	3.4/4.6
XHA17251B11H	Ball	100~125	50/60	0.60	47/41	2700/3000	51/55	272/306	160/180	11.3/13
XHA17251B11M		100~125	50/60	0.50	28/27	2500/2700	49/51	252/272	148/160	9.9/7.0
XHA17251B11L		100~125	50/60	0.40	20/20	2200/2400	45/47	233/240	137/141	3.4/4.6

