

SHENZHEN BRILLIANT CRYSTAL TECHNOLOGIC CO.,LTD.

# 深圳市彩晶科技有限公司

The specification for the following models :

CM162-4BLWAA-5

CM162-4FLWAA-5

CM162-4GLWAA-5

CM162-4ILWAA-5

PROPOSED BY		APPROVED
Design	Approved	

TEL:+86-755-29995238

FAX:+86-755-29459900

Http://www.cj86.com

E-mail:szcj86@gmail.com

Http://www.szcm-lcd.com


E-mail:szcj86@hotmail.com

地址：深圳市南山区西丽留仙洞工业区顺和达厂区 B 栋

1. Mechanical Specification

ITEM	STANDARD VALUE			UNIT
NUMBER OF CHARACTERS	16 CHARACTERS X 2 LINES			--
CHARACTER FORMAT	5 X 8 DOTS			--
MODULE DIMENSION	80.0 (W) X 36.0 (H) X 12.0 (T)			mm
VIEWING DISPLAY AREA	64.6 (W) X 13.8 (H)			mm
ACTIVE DISPLAY AREA	54.84 (W) X 11.14 (H)			mm
CHARACTER SIZE	2.94 (W) X 5.38 (H)			mm
CHARACTER PITCH	3.46 (W) X 5.76 (H)			mm
DOT SIZE	0.54 (W) X 0.62 (H)			mm
DOT PITCH	0.06 (W) X 0.06 (H)			mm
DRIVE METHOD	1/16 Duty , 1/5BIAS			
VIEWING DIRECTION	6 O'clock			
LED Backlight Color	White			
Backlight Input	DC +5.0V	V		mA
LED backlight current	10			mA
Backlight Half-Lift Time	35,000			HR.
INPUT VOLAGE	DC +5.0V	V	1	mA
LCD DRIVER	SPLC780D			
Weight	36g			

2. Mechanical Diagram



## 3. Interface Pin Connections

NO	SYMBOL	LEVEL	FUNCTION
1	VSS	--	GND ( 0V)
2	VDD	--	DC +5V
3	VO	--	Contrast Adjust
4	NC	--	NC
5	CSB	H/L	3-wire SPI chip select ,IIC interface keep floating
6	PSB	H/L	PSB="L" 3SPI interface ,PSB="H" IIC interface
7	NC	-	NC
8	NC	-	NC
9	NC	-	NC
10	NC	-	NC
11	NC	-	NC
12	NC	-	NC
13	SCK	H/L	Serial clock input
14	SDA	H/L	Serial data input
15	LED A	--	+5V (LED Backlight 1)
16	LED K	--	0V(LED Backlight 2)

## 4. Absolute Maximum Ratings

ITEM	SYMBOL	MIN.	TYPE	MAX.	UNIT
OPERATING TEMPERATURE	TOP	0/-20	--	+50/+70	
STORAGE TEMPERATURE	TST	-10/-30	--	+60/+80	
INPUT VOLTAGE	VI	4.75	5.0	5.25	V
SUPPLY VOLTAGE FOR LOGIC	VDD-VSS	--	5.0	5.5	V
SUPPLY VOLTAGE FOR LCD	VDD-VO	--	--	5.0	V
STATIC ELECTRICITY	Be sure that you are grounded when handing LCM.				