

5 位數微電腦型盤面式電錶(24X48mm)

(5 DIGIT MICROPROCESS PANEL METER, 24x48mm)

MODEL
MMS



特點(FEATURES)

- 精確度 0.05%滿刻度±1位數 (Accuracy 0.05% F.S.±1digit)
- 可量測交直流電流/交直流電壓/電位計/傳送器/Pt-100/熱電偶/荷重元/電阻 等信號 (Measuring DCA/DCV/ACA/ACV/Potentiometer/Transmitter/Pt-100/Thermocouple/Load Cell/Resistor/etc.....)
- 顯示範圍 -19999~99999 可任意規劃 (Programmable rate -19999 to 99999 digit)
- 具有自動歸零或保持或雙顯示功能 (Auto zero or hold or dual display function) (optional)
- 小數點可任意規劃 (Decimal point can be modified)
- 尺寸小,穩定性高 (Dimension small and High stability)

1. MODEL: MMS-

(選購型號)

NO	Input Type	NO	DCV(ACV)	NO	DCA(ACA)	NO	Potentiometer	NO	Transmitter	NO	Pt-100	NO	Load Cell	NO	Thermocouple	NO	Aux.Power
A	DC	11	0~50mV	21	0~19.999uA	31	0~10%	41	DC4~20mA	51	-50.00~+50.00	61	2mV/V	71	J(-200~760)	A	AC/DC18~60V
B	AC(RMS)	12	0~5V	22	0~199.99uA	32	0~50%	42	DC1~5V	52	-100.00~+100.00	62	3mV/V	72	K(-200~1360)	B	AC/DC90~260V
C	AC(TRMS)	13	0~10V	23	0~1.9999mA	33	0~100%	43	DC4~20mA	53	-200.0~+400.0	63	2mV/V	73	T(-200~395)		LESS 3VA for AC/DC input
D	Potentiometer	14	0~36V	24	0~19.999mA	34	5~95%	44	DC1~5V	54	-200.0~+850.0	64	3mV/V	74	E(-185~990)		
E	Transmitter	15	0~54V	25	0~199.99mA	35	10~90%	49	SPECIFIED	59	SPECIFIED	69	SPECIFIED	75	R(0~1760)		
F	Pt-100(RTD)	16	0~110V	26	0~2.000A	39	SPECIFIED	41/42 nonexciting DC24V	Three wire connection non-programmable	61/62 Exciting DC5V(<50mA)	76	S(0~1750)					
G	Thermocouple	17	0~600V	27	0~5.000A			43/44 exciting DC24V (<25mA)		63/64 Exciting DC10V(<50mA)	77	B(200~1800)					
H	Load Cell	18	0~1000V	28	0~7.500A												
R	Resistor	19	SPECIFIED	29	SPECIFIED												

2. SPECIFICATION (主要規格)

- Measuring accuracy (精確度) (23±5) : 0.05% F.S.±1 digit
- 0.2% F.S.±1 digit (AC(RMS))
- 0.2% F.S.±0.5 (CJC)(Thermocouple)
- Sampling time (取樣時間) : 16 cycles/sec.
- Readout range (顯示值範圍) : -19999 ~ 99999 digit adjustable
- Zero (offset) range (歸零調整範圍) : -19999 ~ 99999 digit adjustable
- Over input indication (過載顯示) : " doFL " or "-doFL"
- Display (顯示幕) : Red high efficiency LEDs high 10.16mm(.4")
- Polarity display (極性顯示) : When input is negative " _ " display
- Temp. coefficient (溫度係數) : 50ppm/ (0~50)
- Parameter setting (參數設定方式) : Touch switches
- Memory mode (記憶型式) : Non-volatile E² PROM memory
- Dielectric strength (絕緣耐壓能力) : 1.5KVac/1 min. (input/power)
- Operating condition (使用環境條件) : 0~50 (20 to 90% RH non-condensed)
- Storage condition (存放環境條件) : 0~70 (20 to 90% RH non-condensed)
- CE EMC Certification (CE認證) : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3. OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

