



设备特性

1/3" SONY Super HAD CCD II

坚固铝合金外壳, 防损坏

外形美观, 电梯专用

标配3.6MM镜头

伪装性好, 外型美观

最低照度0Lux (LED ON)

分辨率高, 700VL, 图像清晰、细腻符合IP66级防水设计可靠性高

型号	CL-511K CL-511S	CL-511E	CL-511A7	CL-511A8	CL-511A12
成像器件	1/3" SONY Super HAD CCD II	1/3" SONY Exview HAD CCD II +SONY Effi-E DSP	1/4" ADS Pixel Color CMOS	1/4"ADS Pixel Color CMOS+DSP	1/3" 1.3MP Megapixel ADS Color CMOS
像素	PAL: 500(H) X 582(V) NTSC: 512(H) X 492(V)	PAL: 976(H) X 582(V) NTSC: 976(H) X 494(V)	PAL:1020(H)×596(V) NTSC:1020(H)×508(V)	PAL:1024(H)×768(V) NTSC:1024(H)×670(V)	1280*960P
感光面积	4.8mm(H) X 3.6mm(V)		3.6mm(H) X 2.7mm(V)		4.8mm(H) X 3.6mm(V)
水平解析度	520TVL	700TVLwith OSD 菜单	700TVL	800TVL	1200TVL
制式	PAL/NTSC				
最低照度	0 Lux (LED ON)				
信噪比	>48 dB				
电子快门	PAL:1/50-1/100000 sec NTSC: 1/60-1/100000 sec				
增益控制	自动 Auto				
背光补偿	自动 Auto				
白平衡	自动 Auto				
适用场所区域	该监控摄像机适用于道路、商场、银行、公共场所、金融、酒店、写字楼、小区等；室内外各种暗光环境下监控场所及部分条件恶劣的特殊环境				
同步方式	内同步 Internal Synchronization				
工作温度	-20℃~50℃				
镜头	2.8/3.6mm				
电源输入	DC12V 0.3A				
视频输出	1.0Vp-p/75Ω(BNC)				
尺寸	Φ85*56				
重量	207g				



X