


Panel hole size

Panel thickness	X
0.75-1.25	30.0
1.25-2.0	30.2
2.0-3.0	30.5

Panel hole size



连体防水型：IP67

承认SPECIFICATIONS:UL、CUL、ENEC、S

规格RATING:16A250VAC/20A125VAC 3/4HP 250VAC

16(4)A 250VAC T105

接触电阻CONTACT RESISTANCE: 30m $\Omega$  (MAX, INITIAL)

绝缘阻抗INSULATION RESISTANCE: 100M $\Omega$  500VDC (MIN)

耐压强度WITHSTAND VOLTAGE: 1500VAC-1MINUTE

电气寿命LIFE EXPECTANCY: OVER 10, 000 CYCLES

操作力Operation:3-10N

Function	
00	Indicator Lamp
21/N	ON-OFF 4P w/lamp
21	ON-OFF 4P
22	ON-ON 6P
23	ON-OFF-ON 6P
23(ON)	(ON)-OFF-ON 6P
23(2xON)	(ON)-OFF-(ON) 6P

Color	Cap/Housing
	BK Black
	WT White
	RE Red
	OR Orange
	GR Green
	BL Blue

Cap Printing	None
0	□
1	□ ●
2	□ ○
3	□ ○
4	□ -
5	□
6	□   ○
7	□   ○
8	□ ON
15	□ ○

佛山市惠远电器制品有限公司  
Foshan HuiYuan Electric Co., Ltd

地址：佛山市南海区桂城叠北工业区

传真：0757-81807890 电话：0757-63305816

佛山市展远电子有限公司

Foshan City Exhibition far Electronics Co. Ltd.

地址：佛山市南海区华南城D区

网站：<http://www.hydq-china.com/>