

NOTES :


- 1> Specification:
- 1> Operating force: 1000gMax
 - 2> Operating Temperature: -30° to+85°
 - 3> Storage Temperature: -40° to+85°
 - 4> Mechanical Life: 3000cycles minimum

2. PLATING:
 GOLD FLASH 1u"(min.) SOLDERABLE,
 3u" GOLD PLATING ON THE CONTACT AREA,
 WITH 50u" NICKEL UNDERPLATINGOVERALL.

3. PART NUMBER DESCRIPTION

DISC XX T S G E T

- [包装方式: T=管装 R=卷装]
- [电鍍层: B=鍍鍍部3u" G=鍍鍍部3u" 焊鍍部1-2u"]
- [G=鍍金 S=内金外鍍]
- [脚型: S脚 / J脚 / 环脚 / A脚 / Z脚]
- [T=低推贴放 S=低推不贴放 L=长推]
- [产品代码: 02=2P 04=4P 06=6P 08=8P 10=10P 12=12P]



Number	Part Name	Material	Finished
①	Actuator	UL94 VO	White
②	Cover	UL94 VO	Black
③	Movable	Copper Alloy	3u"Gold
④	Terminal	Brass	1u"Gold
⑤	Base	UL94 VO	Black
⑥	Terminal Contact	Brass	3u"Gold

TOLERANCE UNLESS OTHERWISE SPECIFIED		INSPECTION	
LINER	ANGLES	COPY	PROJECTION
.0 ± 0.10	0 ± 1°		
.00 ± 0.05	0 ± 0.5°		
.000± 0.03	.00±		
DESIGN	ER XIN LU	04/12/12	
DRAWING			
CHECK			
APPRO.			

东莞市广智实业有限公司

TITLE
 BY DISC SERIES PITCH 2.54mm
 TYPE HOUSING
 PRODUCT FAMILY DISC SERIES
 PRAT NO. D51C08LHGET
 FILE NO. D51C08LHGET-A
 SIZE UNIT SCALE SHEET REV.
 A4 mm 2 : 1 10F1 A