

## LNE-WS-PE 聚乙烯软管 PE FLEXIBLE PIPE

**产品材质:** PE聚乙烯 (Polyethylene)

**工作温度:** -30℃~+100℃短时可达+120℃

**结构:** 结构内部和外表均为波浪型:

**颜色:** 黑色, 其它颜色可以订做 (根据需要可开口)

**特性:** 柔韧性好, 表面光泽, 耐化学腐蚀性

**应用领域:** 可用于机床机械, 电力设备, 食品机械, 自动化仪, 电机马达, 保护电线电缆不受外力磨损及绝缘

**使用方法:** 将电线电缆插入管内, 配上LNE: SM-G、SM、SM-F系列软管接头对应的型号使用即可



**Product material:** PE (Polyethylene)

**Working temperature:** -30℃~+100℃, +120℃ can be reached but kept only for a short time


**Structure:** Wavy shape both interiorly and exteriorly

**Color:** Black. Other colors are customizable upon requirements.

**Property:** Good flexibility, smooth and bright surface, chemical corrosion resistant

**Application:** It can be used in machineries, electric equipment, foodstuff machineries, automatic meters and gauges, motors, protecting the cables from abrasion and providing insulation to the wires and cables.

**How to use:** Insert the wires and cables into the pipe and fit respective types of LNE: SM-G、SM and SM-F series flexible joints before using.



(Nylon)

## RoHS

型号 Item No.	软管规格(AD) Specifications For Flexible Pipe		内径 × 外径(mm) Inner Diameter × Outer Diameter	弯曲半径(mm) Curved Radius	包装单位(m) Packaging Unit
	AD	规格			
LNE-PE-10.0	AD10.0	1/4"	6.5 × 10.0	16	100
LNE-PE-11.6	AD11.6		8.0 × 11.6	16	100
LNE-PE-13.0	AD13.0	5/16"	10.0 × 13.0	20	100
LNE-PE-15.8	AD15.8	3/8"	12.0 × 15.8	30	100
LNE-PE-18.5	AD18.5		14.3 × 18.5	40	100
LNE-PE-21.2	AD21.2	1/2"	17.0 × 21.2	45	100
LNE-PE-25.0	AD25.0		20.0 × 25.0	45	50
LNE-PE-28.5	AD28.5	3/4"	23.0 × 28.5	50	50
LNE-PE-34.5	AD34.5	1"	29.0 × 34.5	60	50
LNE-PE-42.5	AD42.5	1 1/4"	36.0 × 42.5	70	50
LNE-PE-54.5	AD54.5	2"	48.0 × 54.5	90	25
LNE-PE-74.0	AD74.0	2 1/2"	63.0 × 74.0	130	10
LNE-PE-88.0	AD88.0	3"	76.0 × 88.0	170	10
LNE-PE-108.0	AD108.0	4"	94.0 × 108.0	225	10