



NE-2 标准亮度

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V AC	220-250V AC	
					AC	DC				
Ne-2 3*10	3 (+0.2, -0.2)	10 (+0, -1.5)	0.35	30	65	90	0.3	150	330	25000
Ne-2 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	65	90	0.3	150	330	25000
Ne-2 4*10.5	4 (+0.1, -0.3)	10.5 (+0.5, -1)	0.35	30	65	90	0.3	150	330	25000
Ne-2 5*13	5 (+0.1, -0.3)	13 (+0, -2)	0.40	30	65	90	0.7	68	220	25000
Ne-2 5*16	5 (+0.1, -0.3)	16 (+0.5, -1)	0.40	30	65	90	0.7	68	220	25000
Ne-2 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	65	90	0.7	68	220	25000
Ne-2 6*14	6 (+0.1, -0.3)	14 (+0.5, -1.5)	0.40	30	65	90	0.7	68	220	25000
Ne-2 6*16	6 (+0.2, -0.2)	16 (+0, -1.5)	0.40	30	65	90	0.7	68	220	25000
Ne-2 6*18	6 (+0.2, -0.2)	18 (+0, -1.5)	0.40	30	65	90	0.7	68	220	25000
Ne-2 6*20	6 (+0.2, -0.2)	20 (+0, -1.5)	0.40	30	65	90	0.7	68	220	25000
Ne-2 6*22	6 (+0.2, -0.2)	22 (+0, -1.5)	0.40	30	65	90	0.7	68	220	25000




NE-2 高亮度

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V AC	220-250V AC	
					AC	DC				
Ne-2H 3*10	3 (+0.2, -0.2)	10 (+0, -1.5)	0.35	30	65	95	0.6	68	220	25000
Ne-2H 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	65	95	0.9	47	150	25000
Ne-2H 4*10.5	4 (+0.1, -0.3)	10.5 (+0.5, -1)	0.35	30	65	95	0.9	47	150	25000
Ne-2H 5*13	5 (+0.1, -0.3)	13 (+0, -2)	0.40	30	65	95	0.9	47	150	25000
Ne-2H 5*16	5 (+0.1, -0.3)	16 (+0.5, -1)	0.40	30	65	95	0.9	47	150	25000
Ne-2H 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	65	95	0.9	47	150	25000
Ne-2H 6*14	6 (+0.1, -0.3)	14 (+0.5, -1.5)	0.40	30	65	95	0.9	47	150	25000
Ne-2H 6*16	6 (+0.1, -0.3)	16 (+0.5, -1.5)	0.40	30	65	95	0.9	47	150	25000
Ne-2H 6*18	6 (+0.1, -0.3)	18 (+0.5, -1.5)	0.40	30	65	95	1.1	33	120	25000
Ne-2H 6*20	6 (+0.1, -0.3)	20 (+0.5, -1.5)	0.40	30	65	95	1.1	33	120	25000
Ne-2H 6*22	6 (+0.1, -0.3)	22 (+0.5, -1.5)	0.40	30	65	95	1.1	33	120	25000




NE-2UH 超高亮度

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V AC	220-250V AC	
					AC	DC				
Ne-2UH 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	95	135	3.0	15	47	15000
Ne-2UH 5*12	5 (+0.1, -0.3)	12 (+0.5, -1)	0.40	30	95	135	3.0	15	47	15000
Ne-2UH 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	95	135	4.0	12	39	15000
Ne-2UH 6*16	6 (+0.1, -0.3)	16 (+0.5, -1.5)	0.40	30	95	135	4.0	12	39	15000
Ne-2UH 6*18	6 (+0.1, -0.3)	18 (+0.5, -1.5)	0.40	30	95	135	4.0	12	39	15000
Ne-2UH 6*20	6 (+0.1, -0.3)	20 (+0.5, -1.5)	0.40	30	95	135	4.0	12	39	15000



NE-2B 蓝色荧光灯

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V	220-250V	
					AC	DC		AC	AC	
Ne-2B 3*10.5	3 (+0.2, -0.2)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	15000
Ne-2B 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	15000
Ne-2B 5*13	5 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	15000
Ne-2B 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	15000
Ne-2B 6*14	6 (+0.1, -0.3)	14 (+0.5, -1.5)	0.40	30	85	120	0.7	82	220	15000
Ne-2B 6*16	6 (+0.1, -0.3)	16 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000
Ne-2B 6*18	6 (+0.1, -0.3)	18 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000
Ne-2B 6*20	6 (+0.1, -0.3)	20 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000



NE-2G 绿色荧光辉光灯

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V AC	220-250V AC	
					AC	DC				
Ne-2G 3*10.5	3 (+0.2, -0.2)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	15000
Ne-2G 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	15000
Ne-2G 5*13	5 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	15000
Ne-2G 5*16	5 (+0.1, -0.3)	16 (+0, -1.5)	0.35	30	85	120	0.5	100	220	15000
Ne-2G 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	15000
Ne-2G 6*14	6 (+0.1, -0.3)	14 (+0.5, -1.5)	0.40	30	85	120	0.7	82	220	15000
Ne-2G 6*16	6 (+0.1, -0.3)	16 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000
Ne-2G 6*18	6 (+0.1, -0.3)	18 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000



NE-2Y 黄色荧光辉光灯

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V AC	220-250V AC	
					AC	DC				
Ne-2Y 3*10.5	3 (+0.2, -0.2)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	20000
Ne-2Y 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	20000
Ne-2Y 5*13	5 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	20000
Ne-2Y 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.8	68	180	20000
Ne-2Y 6*14	6 (+0.1, -0.3)	14 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000
Ne-2Y 6*16	6 (+0.1, -0.3)	16 (+0.5, -1.5)	0.40	30	85	120	1.0	47	150	15000
Ne-2Y 6*18	6 (+0.1, -0.3)	18 (+0.5, -1.5)	0.40	30	85	120	1.0	47	150	15000



NE-2W 白色荧光辉光灯

型号 规格	外形尺寸		引出线		电参数			使用条件外接电阻		寿命 h
	直径 (MM)	长度 (MM)	直径 (MM)	长度 (MM)	起辉电压		电流 MA	110-120V AC	220-250V AC	
					AC	DC				
Ne-2W 3*10.5	3 (+0.2, -0.2)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	15000
Ne-2W 4*10	4 (+0.1, -0.3)	10 (+0, -1.5)	0.35	30	85	120	0.5	100	270	15000
Ne-2W 5*13	5 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	15000
Ne-2W 6*13	6 (+0.1, -0.3)	13 (+0, -2)	0.40	30	85	120	0.7	82	220	15000
Ne-2W 6*14	6 (+0.1, -0.3)	14 (+0.5, -1.5)	0.40	30	85	120	0.7	82	220	15000
Ne-2W 6*16	6 (+0.1, -0.3)	16 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000
Ne-2W 6*18	6 (+0.1, -0.3)	18 (+0.5, -1.5)	0.40	30	85	120	0.8	68	180	15000