






PRODUCT NO. DSHPO2TSGE1
RoHS compliant

NOTES :1.Specification:
1>.Operating force:1000gf Max
2>.Operating Temperature: -40° to+85°
3>.Storage Temperature: -40° to+85°
4>.Electrical Life:1000cycles 25mA 24VDC
5>.Mechanical Life:3000cycles Operations

| REV. | ECN NO. | DR | DATE |
|------|---------|----|------|
| | | | |





RECOMMENDED P.C.B. LAYOUT (TOP VIEW)



2. PLATING:
GOLD FLASH 1u"(min.) SOLDER TAIL,
3u" GOLD PLATING ON THE CONTACT AREA,
WITH 50u" NICKEL UNDERPLATING OVERALL.
3. PART NUMBER DESCRIPTION :
DSHP XX I S G E I

[包装方式: T=管装 R=Reel]
[电镀层: B=镀锡层 3u" 焊脚部 1.2u" G=镀镍层 3u" 焊脚部 3u" F=镀镍层 10u" 焊脚部 10u"]
[G=镀金 S=内镀金(接触部) 外镀锡(焊脚部)]
[脚型: S脚 / J脚 / 埋脚 / A脚 / 2脚]
[T=低推贴胶 S=低推不贴胶 L=长推]
[产品P数: 02=2P 04=4P 06=6P 08=8P 10=10P 12=12P]



| | | | | | |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 1 | 2 | 3 | 4 | 5 | 6 |

| Number | Part Name | Material | Finished |
|--------|------------------|------------------|----------|
| ① | Actuator | UL94 V0 | White |
| ② | Cover | UL94 V0 | Black |
| ③ | Movable | Beryllium Copper | 3u" Gold |
| ④ | Terminal | Brass | 1u" Gold |
| ⑤ | Base | UL94 V0 | Black |
| ⑥ | Terminal Contact | Brass | 3u" Gold |
| ⑦ | Mylar | UL94 V0 | 0.05mm |

| TOLERANCE UNLESS OTHERWISE SPECIFIED | | INSPECTION COPY | |
|--------------------------------------|-----------|-----------------|--|
| LINER | ANGLES | PROJECTION | |
| 0 ± 0.25 | 0 ± 2' | | |
| .00 ± 0.15 | .0 ± 1' | | |
| .000± 0.10 | .00± 0.5' | | |
| DESIGN | kathy | 03/20/12 | |
| DRAWING | | | |
| CHECK | | | |
| APPRO. | | | |

| | | | | | |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 1 | 2 | 3 | 4 | 5 | 6 |

东莞市广智实业有限公司
Dongguan Kingtek Industrial Co., Ltd.

TITLE
BY DSHP SERIES PITCH 1.27mm
PRODUCT FAMILY DSHP SERIES
PRAT NO. DSHPO2TSGE1
FILE NO. DSHPO2TSGE1-A
SIZE UNIT SCALE SHEET REV.
A4 mm Z : 1 1OF 1 A