



PIN CONNECTIONS

Pin	Symbol	Level	Function
1	VSS	0V	Ground
2	VDD	5V	Power supply for Logic
3	/REST	L	Reset signal ,active "L"
4	D/C	H/L	Data/Command select
5	/WR	L	8080: Write signal
6	/RD	L	8080: Read signal
7	DB0	H/L	Data bus line
14	DB7		Serial mode :D1-SI D0-SCL
15	/CS		L
16 20	NC		No connection

NOTES:

1. Built-in SSD1325 controller
2. 3.3V/5V power supply optional
3. Parallel / Serial interface optional
4. Display color : YELLOW/GREEN

MECHANICAL DATA

Item	Nominal Dimensions	Unit
Module Size (W x H x T)	85.0X58.0X8.0	mm
Viewing Area (W x H)	65.0X33.0	mm
Dot Pitch (W x H)	0.48X0.48	mm
Dot Size (W x H)	0.455X0.455	mm

ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Min.	Max.	Unit
Supply Voltage (Logic)	$V_{DD}-V_{SS}$	0	3.5	V
Supply Voltage(OLED)	$V_{CC}-V_{SS}$	0	16.0	V
Input Voltage	V_I	0	V_{DD}	V
Operating Temp.	T_{OPR}	-40	+70	°C
Storage Temp.	T_{STG}	-40	+80	°C

ELECTRICAL CHARACTERISTICS ($V_{DD}=5.0V, T_a=25^\circ C$)

Item	Symbol	Min.	Typ.	Max.	Unit
Input High Voltage	V_{IH}	0.8 V_{DD}	-	V_{DD}	V
Input Low Voltage	V_{IL}	0	-	0.2 V_{DD}	V
Output High Voltage	V_{OH}	0.9 V_{DD}	-	V_{DD}	V
Output Low Voltage	V_{OL}	0	-	0.1 V_{DD}	V
Supply Current	I_{DD}	-	TBD	-	mA
OLED Display Voltage	$V_{CC}-V_{SS}$	12.5	13.0	13.5	V