

M39xx 大量程六轴力传感器

产品描述

量程:2.7KN ~ 145.7KN,120Nm ~ 13.5KNm

非线性和迟滞优于 1%

串扰:5%

结构解耦，大量程，小尺寸直径 60mm ~ 135mm

标准保护等级 IP60，可选择保护等级 IP68 用于水下 10m



选型指南，如需详细产品信息，请联系我们！

Model #	Model Description	Capacity				Dimension (mm)			MASS (KG)
		FX,FY (N)	FZ (N)	MX,MY (Nm)	MZ (Nm)	OD	Height	ID	
3923	6 AXIS LOADCELL D60MM F2700N	2700	5400	120	96	60	40	15	0.18
3924	6 AXIS LOADCELL D90MM F2700N	2700	5400	180	144	90	40	35	0.37
3925	6 AXIS LOADCELL D135MM F2700N	2700	5400	270	216	135	40	70	0.72
3933	6 AXIS LOADCELL D60MM F5400N	5400	10800	240	192	60	40	15	0.48
3934	6 AXIS LOADCELL D90MM F5400N	5400	10800	360	288	90	40	35	0.99
3935	6 AXIS LOADCELL D135MM F5400N	5400	10800	540	432	135	40	70	1.95
3943	6 AXIS LOADCELL D60MM F16200N	16200	32400	660	530	60	50	15	0.62
3944	6 AXIS LOADCELL D90MM F16200N	16200	32400	1000	800	90	50	35	1.30
3945	6 AXIS LOADCELL D135MM F16200N	16200	32400	1500	1200	135	50	57	2.90
3954	6 AXIS LOADCELL D90MM F48600N	48600	97200	3000	2400	90	75	33	2.20
3955	6 AXIS LOADCELL D135MM F48600N	48600	97200	4500	3600	135	75	57	5.00
3965	6 AXIS LOADCELL D135MM F145800N	145800	291600	13500	10800	135	120	47	7.40

