



P.C.B. LAYOUT

SPECIFICATIONS

Current Rating: 0.5A AC,DC
 Voltage Rating: 30V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 200V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Solder Tabs: Phosphor Bronze/Tin-plated
 Material: LCP,UL94V-0
 Color: Natural (Beige)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A0800WR-S-02P	0.80	3.80
A0800WR-S-03P	1.60	4.60
A0800WR-S-04P	2.40	5.40
A0800WR-S-06P	4.00	7.00
A0800WR-S-07P	4.80	7.80
A0800WR-S-08P	5.60	8.60
A0800WR-S-10P	7.20	10.20
A0800WR-S-12P	8.80	11.80
A0800WR-S-14P	10.40	13.40
A0800WR-S-15P	11.20	14.20
A0800WR-S-16P	12.00	15.00
A0800WR-S-17P	12.80	15.80
A0800WR-S-20P	15.20	18.20

东莞市尚宇电子有限公司

UNIT	SCALE	SHEET	TITLE:
mm		1 of 2	
DRAWN BY	APPROVED BY		0.80mm PITCH 90°WAFER-SMT TYPE
GENERAL TOLERANCE			
X.X±0.25	ANGLE±		
X.XX±0.15			DRAW NO.: A0800WR-S-XP
X.XXX±0.05			
REV.	DESCRIPTION	DATE	REV. A4