



PIN CONNECTIONS

Pin	Symbol	Level	Function
1	V _{SS}	0V	Ground
2	V _{DD}	3.3V	Power supply for Logic
3	NC	-	No connection
4	A0	H/L	Data/Command select
5	/WR	L	8080: Write signal
6	/RD	L	8080: Read signal
7	DB0	H/L	Data bus line
14	DB7		Serial mode :D1-S1 D0-SCL
15	/CS	L	Chip select signal
16	/REST	L	Reset signal ,active "L"
17	BS0	H/L	BS0 、 BS1: interface select: 01:8080 parallel 11:6800 parallel 00: Serial
18	BS1	H/L	
19	NC	-	
20	NC	-	No connection

MECHANICAL DATA

Item	Nominal Dimensions	Unit
Module Size (W x H x T)	163.5X54.0X9.5	mm
Viewing Area (W x H)	137.6X35.7	mm
Dot Pitch (W x H)	0.53X0.53	mm
Dot Size (W x H)	0.50X0.50	mm

ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Min.	Max.	Unit
Supply Voltage (Logic)	V _{DD} -V _{SS}	0	4.0	V
Supply Voltage(OLED)	V _{CC} -V _{SS}	0	16.0	V
Input Voltage	V _I	0	V _{DD}	V
Operating Temp.	T _{OPR}	-30	+70	°C
Storage Temp.	T _{STG}	-40	+80	°C

ELECTRICAL CHARACTERISTICS (V_{DD}=3.3V, T_a=25°C)

Item	Symbol	Min.	Typ.	Max.	Unit
Input High Voltage	V _{IH}	0.8 V _{DD}	-	V _{DD}	V
Input Low Voltage	V _{IL}	V _{SS}	-	0.2V _{DD}	V
Output High Voltage	V _{OH}	0.9 V _{DD}	-	V _{DD}	V
Output Low Voltage	V _{OL}	V _{SS}	-	0.1V _{DD}	V
Supply Current	I _{DD}	-	TBD	-	mA
OLED Display Voltage (GREEN)	V _{CC} -V _{SS}	14.5	15.0	15.5	V

NOTES:

1. Built-in SSD1322 controller
2. 3.3V/5.0V power supply optional
3. Parallel / Serial interface optional
4. Display color : GREEN