


PIN ASSIGNMENT

| | |
|----|--------|
| 1 | VCC |
| 2 | VCC |
| 3 | VCC |
| 4 | VCC |
| 5 | CS(5) |
| 6 | CS(6) |
| 7 | CS(7) |
| 8 | CS(8) |
| 9 | CS(9) |
| 10 | CS(10) |
| 11 | CS(11) |
| 12 | CS(12) |
| 13 | CS(13) |
| 14 | CS(14) |
| 15 | CS(15) |
| 16 | CS(16) |
| 17 | CS(17) |
| 18 | CS(18) |
| 19 | CS(19) |
| 20 | CS(20) |
| 21 | CS(21) |
| 22 | CS(22) |
| 23 | CS(23) |
| 24 | CS(24) |
| 25 | CS(25) |
| 26 | CS(26) |
| 27 | CS(27) |
| 28 | CS(28) |
| 29 | CS(29) |
| 30 | CS(30) |
| 31 | CS(31) |
| 32 | CS(32) |
| 33 | CS(33) |
| 34 | CS(34) |
| 35 | CS(35) |
| 36 | CS(36) |
| 37 | CS(37) |
| 38 | CS(38) |
| 39 | CS(39) |
| 40 | CS(40) |

- Unit: mm.
- Modification rev. number.
- All radii without dimension R0.3mm.
- All draft angles to be 1.5°
- Unspecified Tolerances is : ± 0.30mm.
- Driver IC: ST7789V
- LCD Driver Voltage : 2.8 ± 0.2V
- Color : White
- Operating Temperature : -20° -- +70° C
- Storage Temperature : -30° -- +80° C



| | |
|------------|------|
| 杭州佳显科技有限公司 | |
| 制 图 | 型 号 |
| 审 核 | 编 号 |
| 批 准 | 日 期 |
| | 分 号 |
| | 单 位 |
| | 页 数 |
| | 1/2 |
| | 未注公差 |
| | ±0.3 |