



Recommended P.C. Board Layout

PIN.	Dimension		
	A	B	C
2P	1.20	4.30	2.64
3P	2.40	5.50	3.84
4P	3.60	6.70	5.04
5P	4.80	7.90	6.24
6P	6.00	9.10	7.44
7P	7.20	10.30	8.64
8P	8.40	11.50	9.84

- ◆ SPECIFICATIONS
 - Current rating: 1.5A AC, DC
 - Voltage rating: 50V AC, DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 100MΩ Min.
 - Withstanding voltage: 500V AC/minute.
 - Contact resistance: 20mΩ Max.
- Material:
 Insulator: PA9T UL 94V-0 Black
 Contact: Phosphor bronze
 Fitting Nail: Brass
- Plating:
 Contact: Gold Flash plated
 Fitting Nail: Tin plated
- Circuits: 2~8
 Suitable: 1201 series Housing

GENERAL TOLERANCE		UNIT: mm		TITLE:	
.X±0.30	X°±1°	DRAWN:	王钰徽	DATE:	2015.07.07
.XX±0.20	.X°±	CHECKED:		VER.	A
.XXX±0.10	.XX°±	APPROVED:	周志龙	SCALE:	N/A
VERSION RECORD		DRAWING NO.:		SHEET:	
2015.4.29 按实物修改B号尺寸,系列PIN尺寸加0.10		1201VH/HS101-2-S		1/1	

东莞市康瑞电子有限公司
 Dongguan A Rui Electronic Co., LTD.

4		
3		
2		
1	NAME	DATE

PROJECT		PART NO.		DRAWING NO.	
A		C1201RS***24P9*0		1201VH/HS101-2-S	

LTR		VERSION RECORD		DATE	
1		2		3	
1		2		3	