



### Specifications

Impedance: 50 Ohms  
 Frequency Range: DC~3G  
 VSWR: 1.3MAX  
 Working Voltage: 500V rms @ sea level  
 Insulation Resistance: 5000 Ohms min  
 Temperature Range: -55°C T0 +155°C  
 Relative Temperature: ≤95% (40°C ±2° C)  
 Drawings products are in line with ROHS standards

NOTE:

DRAWN	2012/11/10	Tolerance	0-6 6-30 30-120	±0.10 ±0.20 ±0.40
CHECKED		View	Angul ar	±2°
APPROVALS		UNIT		MM
John Kine	12/04.2012	SCALE		1:1

**Dosin Industrial(H.K)Co.Ltd**  
 东莞市德奈五金电子有限公司  
**Dosin Hardware Electronics Co.,Ltd**  
 E-mail: dosin2005@163.com  
 dosin2005@dosin-china.com  
 Web: http://www.dosinconn.com  
 TEL: (0086) 769-81753906  
 FAX: (0086) 769-81875836

Name: BNC CONNECTOR

SIZE	Product NO.	CAD FILE	SHEET: 1 OF 1
A	DOSIN-801-0018	D:/company drawings/BD	
Date/Time			
2012/11/02			

6	Insulator	POM	-----	8
5	Solder column	Iron	NICKEL	8
4	IRON PLATES	Iron	NICKEL	1
3	PANEL	ABS	BLACK	1
2	PIN	BRASS	NICKEL	8
1	BODY	ZINC	NICKEL	8
NO	DESCRIPTION	MATERIAL	FINISH	QTY

A B C D E F G

Product NO.		DOSIN-801-0018		
REV	DESCRIPTION	DWN	DATE	APPROVEN
A	First Issue	JIM	2012/11/02	John kine