



VOLTAGE RANGE: 100 - 200V
CURRENT: 3.0 A

Features

- High current capability
- High surge current capability
- High reliability
- Low reverse current
- Low forward voltage drop
- Super fast recovery time

Mechanical Data

- Case : DO-201AD Molded plastic
- Epoxy : UL94V-O rate flame retardant
- Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- Polarity : Color band denotes cathode end
- Mounting position : Any
- Weight : 1.21 grams



DO-201AD		
Dim	Min	Max
A	25.40	—
B	7.20	9.50
C	1.20	1.30
D	4.80	5.30
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	FGP30B	FGP30C	FGP30D	Unit
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	100	150	200	Volts
Maximum RMS Voltage	V _{RMS}	70	105	140	Volts
Maximum DC Blocking Voltage	V _{DC}	100	150	200	Volts
Maximum Average Forward Current 0.375"(9.5mm) Lead Length T _a = 55 °C	I _{F(AV)}	3.0			Amps.
Peak Forward Surge Current, 8.3ms Single half sine wave Superimposed on rated load (JEDEC Method)	I _{FSM}	125			Amps.
Maximum Peak Forward Voltage at I _F = 3.0 A.	V _F	0.95			Volts
Maximum DC Reverse Current T _a = 25 °C at Rated DC Blocking Voltage T _a = 100 °C	I _R	5			μA
	I _{R(H)}	50			μA
Maximum Reverse Recovery Time (Note 1)	T _{rr}	35			ns
Typical Junction Capacitance (Note 2)	C _J	50			pf
Junction Temperature Range	T _J	- 65 to + 150			°C
Storage Temperature Range	T _{STG}	- 65 to + 150			°C

Notes :

- (1) Reverse Recovery Test Conditions : I_F = 0.5 A, I_R = 1.0 A, I_{rr} = 0.25 A.
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 V_{bc}

Ratings and Characteristics Curves ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise specified)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance




Figure 4. Typical Reverse Leakage Characteristics




Figure 6. Typical Transient Thermal Impedance